# The City of Oceanside Water Quality Report 2015



The City of Oceanside is committed to providing you with safe drinking water.

We are pleased to report that your drinking water meets or exceeds all state and federal health standards for water quality.

Este informe contiene información muy importante sobre su agua potable. Tradúzcalo o hable con alguien que lo entienda bien.

Your water is routinely tested for about 90 different substances to ensure that the water is of the highest quality. This report lists the substances that were detected during 2015 and includes details about where your water comes from. For more information about your water, contact Robert Gutierrez at (760) 435-5987.

#### **HEALTH INFORMATION**

Some people may be more vulnerable to contaminants in drinking water than the general population. Immuno-compromised persons such as persons with cancer undergoing chemotherapy, persons who have undergone organ transplants, people with HIV/AIDS or other immune system disorders, some elderly, and infants can be particularly at risk from infections. These people should seek advice about drinking water from their health care providers. USEPA/Centers for Disease Control (CDC) guidelines on appropriate means to lessen the risk of infection by Cryptosporidium and other microbial contaminants are available from the Safe Drinking Water Hotline at (800) 426-4791.



#### **WATER SOURCES**

The City of Oceanside has three sources of drinking water. The primary source is imported water that is purchased untreated from the San Diego County Water Authority (SDCWA). This raw water is then treated

at Oceanside's Robert A. Weese (R. A.Weese) water treatment plant. This facility filters and disinfects surface water from lakes and rivers, supplying about 43% of the drinking water used by the people of Oceanside.



The second source is Oceanside's Mission Basin Desalting Facility (MBDF). This facility treats brackish groundwater from wells located in the San Luis Rey River valley. The groundwater is purified by reverse osmosis and then disinfected. The MBDF supplies about 13% of the drinking water used in Oceanside. The third source is treated drinking water purchased directly from SDCWA. About 44% of the treated water used in Oceanside is purchased from SDCWA.

#### **IMPORTED WATER**

Approximately 87% of the water we use in Oceanside is imported from hundreds of miles away. This is "surface water" from rivers and streams in Northern California and the Colorado River Basin.

The Metropolitan Water District (MWD) imports this water to Southern California via a 242-mile-long aqueduct that carries Colorado River water from Lake Havasu, and a 444-mile-long aqueduct bringing water from the Sacramento-San Joaquin Delta. Both aqueducts terminate in Lake Skinner in Riverside County, where these waters are

combined. SDCWA purchases this imported water from MWD and distributes it to water agencies throughout San Diego County, including the City of Oceanside.

#### SOURCE WATER ASSESSMENT

In December 2002, MWD completed its source water assessment of its Colorado River and State Water Project supplies. Colorado River supplies are considered to be most vulnerable to contamination from recreation, urban/storm water runoff, increasing urbanization in the watershed, and wastewater. State Water Project supplies are considered to be most vulnerable to urban/storm water runoff, wildlife, agriculture, recreation and wastewater. A summary of the assessment can be obtained by contacting MWD by phone at (213) 217-5696.

# Water Quality Report 2015

#### **GROUND WATER ASSESSMENT**

An assessment of the current groundwater sources for the City of Oceanside was completed in February 2002. The sources are considered most vulnerable to contamination from sewer collections and/or agricultural/ irrigation wells. A copy of the complete assessment is available at the City of Oceanside Water Utilities Department at 300 North Coast Highway in Oceanside. You may request a summary of the assessment by calling (760) 435-5800.

The Oceanside Utilities Commission meets bi-monthly in the City Council Chambers, at 300 North Coast Highway. The public is welcome to participate in these meetings.

## FOR MORE INFORMATION

Please call (760) 435-5800.

Oceanside's Water Meets Stringent Federal and State Water Requirements



#### **FLUORIDE**

Oceanside has three sources of water: raw water that is treated at the R. A. Weese water treatment plant; groundwater that is treated at the MBDF; and treated water purchased from SDCWA. Oceanside does not add fluoride during treatment at R. A. Weese or the MBDF. The fluoride found in these raw water sources is naturally occurring at 0.3 ppm. The third source is imported treated water from SDCWA. Only the imported treated water has added fluoride.

The area south of Oceanside Blvd. usually receives this fluoridated water with an average concentration of 0.8 ppm. The water delivered to all other areas in the City usually has an average fluoride level of 0.3 ppm. However, when the City's treatment plants are not operating at full capacity, some or all of the water supply for Oceanside can contain added fluoride up to 0.8 ppm.



#### LEAD

The drinking water is tested for lead every three years and was last tested in 2015. Samples were collected inside 50 private homes and at the entry points to the water distribution system. There was no lead detected in the water entering the distribution system, but some of the homes had very small amounts of lead detected. None of the homes exceeded the Action Level (15 ppb) for lead. Lead in drinking water is primarily from materials and components associated with service lines and home plumbing. If present, elevated levels of lead can cause serious health problems, especially for pregnant women and young children. Oceanside is responsible for providing high quality drinking water, but cannot control the variety of materials used in home plumbing components. When your water has been sitting for several hours, you can minimize the potential for lead exposure by flushing your tap for 30 seconds to 2 minutes before using water for drinking or cooking. If you are concerned about lead in your water, you may wish to have your water tested. Information on lead in drinking water, testing methods, and steps you can take to minimize exposure is available from the Safe Drinking Water Hotline or at www.epa.gov/safewater/lead

#### CONTAMINANTS IN DRINKING WATER

Drinking water, including bottled water, may reasonably be expected to contain at least small amounts of some contaminants. The presence of contaminants does not necessarily indicate that water poses a health risk. In order to ensure that tap water is safe to drink, the USEPA and the State Water Resources Control Board prescribe regulations which limit the amount of certain contaminants in water provided by public water systems. More information about contaminants and potential health effects can be obtained by calling the USEPA's Safe Drinking Water Hotline (1-800-426-4791) or at www.epa.gov/safewater.

#### **CONTAMINANTS IN SOURCE WATER**

The sources of tap water and bottled water include rivers, lakes, streams, springs and wells. Water, as it travels over the surface or through the ground, can pick up or dissolve natural minerals and, in some cases, radioactive material, and can pick up substances resulting from the presence of animals or from human activity.

#### Contaminants that may be found in source water include the following:

**Microbial** contaminants, such as viruses and bacteria that may come from sewage treatment plants, septic systems, agricultural livestock operations and wildlife.

**Inorganic** contaminants, such as salts and metals, which can be naturally-occurring or result from urban storm water runoff, industrial or domestic wastewater discharges, oil and gas production, mining or farming.

**Pesticides and herbicides**, which may come from a variety of sources such as agriculture, urban storm water runoff and residential uses.

Organic chemical contaminants, including synthetic and volatile organic chemicals that are by-products of industrial processes and petroleum production, and can also come from gas stations, urban

storm water runoff, agricultural application and septic systems.

Radioactive contaminants, which can be naturally-occurring or be the result of oil and gas production and mining activities.



								Source Wate	rs		
			PHG				Mission	oource wate	SDCWA		
		MCL	(MCLG)	State	Range	R.A. Weese	Basin Desalting	Twin Oaks	Skinner	Carlsbad Desalination	
	Unit	[MRDL]	[MRDLG]	DLR	Average	Plant	Facility	Valley Plant	Plant	Plant	Sources in Drinking Water
PRIMARY S	TANDA	RDS N	landator	y Healt	h-related S	tandards	0.40	0.00	0.40	0.04	T
Turbidity (a)	NTU	TT	NA NA	NA	Highest %<0.3 NTU	0.15 100%	0.10 100%	0.02 100%	0.10 100%	0.04 100%	Soil runoff.
INORGANIC					7	15575	10075				
					Range	ND - 220	ND	ND	ND	ND	Residue from water treatment
Aluminum (b)	ppb	1000	600	50	Average	125	ND	ND	ND	ND	process; Erosion of natural deposits.
Arsenic	ppb	10	0.004	2	Range Average	NA ND	NA ND	NA 3.0	ND ND	ND ND	Leaching from natural deposits
	1,1				Range	NA	NA	NA	NA	ND	,
Barium	ppb	1000	2000	100	Average	130	ND	120	124	ND	Erosion of natural deposits.
Fluoride Natural		2	1	0.1	Range Average	0.2 - 0.4	ND - 0.1 0.1	0.3	0.2-0.4	0.9 - 1.1 NA	Erosion of natural deposits.
Fluoride (c)	ppm	2	Optim			NA	NA	0.6 - 1.0	0.5-0.9	0.5–1.0	Erosion of natural deposits.
Added	ppm	2	1	0.1	Range	Not added	Not added	0.8	0.7	0.8	Water additive for dental health.
					Range	ND - ND	1.5 - 4.2	ND - 0.3	ND	0.7-0.9	Runoff & leaching from fertilizer use;
Nitrate as N	ppm	10	10	0.4	Average	ND Pan	1.9	ND s sampled = NC	ND 0.69	0.8	sewage; erosion of natural deposits.  Internal corrosion of household
Copper (d)	ppm	1.3 (AL)	0.3	0.05	Range for 50 homes sampled = ND - 0.69 90th percentile for 50 homes sampled = 0.21						plumbing; erosion of natural deposits.
		` ′						s sampled = NI			Internal corrosion of household
Lead (d)	ppb	15 (AL)	0.2	5		90th (	percentile for 50	) homes sample	ed = 0.8		plumbing; erosion of natural deposits.
MICROBIOLO Total Coliform	GICAL				Pango		Diotale	ution System -	ND ND		Natural bacteria found in the
Bacteria (e)	%	5.0	0	NA	Range Average			ution System = ribution System			Natural bacteria found in the environment.
RADIOLOGICA								. ,			·
					Range	NA	NA	ND	ND - 5	ND	
Gross Alpha	pCi/L	15	none	3	Average	2.3 NA	0.54 NA	ND ND	ND 5	ND ND	Erosion of natural deposits.
Gross Beta(g)	pCi/L	50	none	4	Range Average	NA NA	NA NA	ND ND	5	ND ND	Decay of natural and man-made products.
					Range	NA	NA	1.7 - 2.3	1 - 2	ND	
Uranium	pCi/L	20	0.43	1	Average	3.6	3.6	2	2	ND	Erosion of natural deposits
Disinfection b	by Produc		I	ı	l	D'ata	the time O return		1 00		D
Total Chlorine (i)	ppm	(RAA) [4.0]	[4.0]	NA			-	wide range = 0. m highest RAA			By-product of drinking water chlorination.
Haloacetic	FF	(LRAA)	[]					m wide range =			By-product of drinking water
acids (h)	ppb	60	NA	1				n highest LRAA			chlorination.
Total Trihalo- methanes (h)	nnh	(LRAA) 80	NA	1				n wide range = : n highest LRAA			By-product of drinking water chlorination.
SECONDAR	ppb XX STAN	DARDS			andards	DIS	uibulion Systei	II Iligilest ERAA	. – 37		Ciloniation.
					Range	85 - 95	108 - 144	NA	102–105	40-54	Runoff/leaching from natural
Chloride	ppm	500	NA	NA	Average	91	133	110	104	44	deposits; seawater influence
Color	Units	15	NA	NA	Range Average	ND	ND ND	ND	1	ND	
Total	Office			11/					1		Naturally occurring organic materials
Hardness						ND 200 - 320		ND NA	1 290–307	ND 40-60	Naturally occurring organic materials
	ppm	NA	NA	NA	Range Average	200 - 320 283	170 - 240 205	NA NA 310	1 290–307 299	ND 40-60 50	Naturally occurring organic materials  Leaching from natural deposits
Total	grains/	NA			Range Average Range	200 - 320 283 12 - 19	170 - 240 205 10 - 14	NA 310 NA	290–307 299 17 - 18	40-60 50 2-4	Leaching from natural deposits
			NA NA	NA NA	Range Average Range Average	200 - 320 283 12 - 19 16	170 - 240 205 10 - 14 12	NA 310 NA 18	290–307 299 17 - 18 17	40-60 50 2-4 3	
Total	grains/	NA			Range Average Range	200 - 320 283 12 - 19	170 - 240 205 10 - 14	NA 310 NA	290–307 299 17 - 18	40-60 50 2-4	Leaching from natural deposits
Total Hardness Odor	grains/ gal	NA NA	NA NA	NA 1	Range Average Range Average Range Average Average Range	200 - 320 283 12 - 19 16 ND ND 191 - 275	170 - 240 205 10 - 14 12 ND ND 89 - 115	NA 310 NA 18 NA 2	290–307 299 17 - 18 17 2 2 237–249	40-60 50 2-4 3 ND ND 15-18	Leaching from natural deposits  Leaching from natural deposits  Naturally occurring organic materials  Runoff/leaching from natural
Total Hardness Odor Sulfate	grains/ gal	NA NA	NA	NA	Range Average Range Average Range Average Average Average Average	200 - 320 283 12 - 19 16 ND ND 191 - 275 249	170 - 240 205 10 - 14 12 ND ND 89 - 115	NA 310 NA 18 NA 2 NA 250	290–307 299 17 - 18 17 2 2 237–249 243	40-60 50 2-4 3 ND ND 15-18	Leaching from natural deposits  Leaching from natural deposits  Naturally occurring organic materials  Runoff/leaching from natural deposits; seawater influence
Total Hardness Odor Sulfate Total Dis-	grains/ gal TON	NA NA 3 500	NA NA	NA 1 0.5	Range Average Range Average Range Average Average Range Average Range Average Range	200 - 320 283 12 - 19 16 ND ND 191 - 275	170 - 240 205 10 - 14 12 ND ND 89 - 115	NA 310 NA 18 NA 2	290–307 299 17 - 18 17 2 2 237–249	40-60 50 2-4 3 ND ND 15-18	Leaching from natural deposits  Leaching from natural deposits  Naturally occurring organic materials  Runoff/leaching from natural
Total Hardness Odor Sulfate	grains/ gal	NA NA	NA NA	NA 1	Range Average Range Average Range Average Average Average Average	200 - 320 283 12 - 19 16 ND ND 191 - 275 249 NA 640	170 - 240 205 10 - 14 12 ND ND 89 - 115 104 NA 430	NA 310 NA 18 NA 2 NA 250 NA	290–307 299 17 - 18 17 2 2 237–249 243 639–655 647	40-60 50 2-4 3 ND ND 15-18 17 120-218	Leaching from natural deposits  Leaching from natural deposits  Naturally occurring organic materials Runoff/leaching from natural deposits; seawater influence Runoff/leaching from natural
Total Hardness  Odor  Sulfate Total Dissolved Solids  Turbidity	grains/ gal  TON  ppm  ppm	NA NA 3 500 1000 5	NA NA NA NA	NA 1 0.5 NA NA	Range Average Range Average Average Range Average Range Average Range Average Average Average	200 - 320 283 12 - 19 16 ND ND ND 191 - 275 249 NA 640 Distrib	170 - 240 205 10 - 14 12 ND ND 89 - 115 104 NA 430 suttion System w	NA 310 NA 18 NA 2 NA 250 NA 690	290–307 299 17 - 18 17 2 2 237–249 243 639–655 647 15 - 0.40	40-60 50 2-4 3 ND ND 15-18 17 120-218	Leaching from natural deposits  Leaching from natural deposits  Naturally occurring organic materials Runoff/leaching from natural deposits; seawater influence Runoff/leaching from natural
Total Hardness  Odor  Sulfate Total Dissolved Solids  Turbidity  UNREGULA	grains/ gal  TON  ppm  ppm	NA NA 3 500 1000 5	NA NA NA NA	NA 1 0.5 NA	Range Average Range Average Range Average Range Average Range Average Average Range Average	200 - 320 283 12 - 19 16 ND ND 191 - 275 249 NA 640 Distrit	170 - 240 205 10 - 14 12 ND ND 89 - 115 104 NA 430 uution System v	NA 310 NA 18 NA 2 NA 250 NA 690 vide range = 0.0 wide average	290–307 299 17 - 18 17 2 2 237–249 243 639–655 647 15 - 0.40	40-60 50 2-4 3 ND ND 15-18 17 120-218	Leaching from natural deposits  Leaching from natural deposits  Naturally occurring organic materials  Runoff/leaching from natural  deposits; seawater influence  Runoff/leaching from natural  deposits; seawater influence  Soil runoff
Total Hardness  Odor  Sulfate Total Dissolved Solids Turbidity	grains/ gal  TON  ppm  ppm	NA NA 3 500 1000 5	NA NA NA NA	NA 1 0.5 NA NA	Range Average Range Average Average Range Average Range Average Range Average Average Average	200 - 320 283 12 - 19 16 ND ND ND 191 - 275 249 NA 640 Distrib	170 - 240 205 10 - 14 12 ND ND 89 - 115 104 NA 430 suttion System w	NA 310 NA 18 NA 2 NA 250 NA 690	290–307 299 17 - 18 17 2 2 237–249 243 639–655 647 15 - 0.40	40-60 50 2-4 3 ND ND 15-18 17 120-218	Leaching from natural deposits  Leaching from natural deposits  Naturally occurring organic materials  Runoff/leaching from natural deposits; seawater influence  Runoff/leaching from natural deposits; seawater influence
Total Hardness  Odor  Sulfate Total Dissolved Solids  Turbidity  UNREGULA	grains/ gal  TON  ppm  ppm  NTU	NA  NA  3  500  1000  5  NTAMIN	NA N	NA  1  0.5  NA  NA  UCMR	Range Average Range Average Range Average Range Average Average Range Average Range Average Average Range Average	200 - 320 283 12 - 19 16 ND ND 191 - 275 249 NA 640 Distrib Distrib 28 - 41 34 4.2 - 4.7	170 - 240 205 10 - 14 12 ND ND 89 - 115 104 NA 430 pution System v ribution System NA 100 NA	NA 310 NA 18 NA 2 NA 250 NA 690 vide range = 0.0 vide average	290–307 299 17 - 18 17 2 2 237–249 243 639–655 647 15 - 0.40 = 0.10	40-60 50 2-4 3 ND ND 15-18 17 120-218 194	Leaching from natural deposits  Leaching from natural deposits  Naturally occurring organic materials  Runoff/leaching from natural deposits; seawater influence  Runoff/leaching from natural deposits; seawater influence  Soil runoff  By product of drinking water chlorination.
Total Hardness  Odor  Sulfate Total Dissolved Solids  Turbidity UNREGULA Chlorate  Molybdenum	grains/ gal  TON  ppm  ppm  NTU	NA  NA  3  500  1000  5  NTAMIN	NA N	NA  1  0.5  NA  NA  UCMR	Range Average Range Average Range Average Range Average Average Range Average Average Average Average Average	200 - 320 283 12 - 19 16 ND ND 191 - 275 249 NA 640 Distrib Distrib 28 - 41 34 4.2 - 4.7	170 - 240 205 10 - 14 12 ND ND 89 - 115 104 NA 430 oution System v ribution System NA 100 NA 3.0	NA 310 NA 18 NA 2 NA 250 NA 690 vide range = 0.0 vide average	290–307 299 17 - 18 17 2 2 237–249 243 639–655 647 15 - 0.40 = 0.10	40-60 50 2-4 3 ND ND 15-18 17 120-218 194	Leaching from natural deposits  Leaching from natural deposits  Naturally occurring organic materials  Runoff/leaching from natural deposits; seawater influence  Runoff/leaching from natural deposits; seawater influence  Soil runoff  By product of drinking water
Total Hardness  Odor  Sulfate Total Dissolved Solids  Turbidity  UNREGULA Chlorate	grains/ gal  TON  ppm  ppm  NTU  TED CO  ppb	NA  NA  3  500  1000  5  NTAMIN  NA	NA NA NA NA NA NA JANTS ( 210	NA  1  0.5  NA  NA  UCMRE 20  NA	Range Average Range Average Range Average Range Average Range Average Average Average Average Average Average Average Range Average Range Average Range Average Range	200 - 320 283 12 - 19 16 ND ND 191 - 275 249 NA 640 Distrit 28 - 41 34 4.2 - 4.7 4.4	170 - 240 205 10 - 14 12 ND ND 89 - 115 104 NA 430 sution System v ribution System NA 100 NA 3.0 NA	NA 310 NA 18 NA 2 NA 250 NA 690 vide range = 0.00 vide average 130-320 220 NA NA	290–307 299 17 - 18 17 2 2 237–249 243 639–655 647 15 - 0.40 = 0.10	40-60 50 2-4 3 ND ND 15-18 17 120-218 194	Leaching from natural deposits  Leaching from natural deposits  Naturally occurring organic materials  Runoff/leaching from natural deposits; seawater influence  Runoff/leaching from natural deposits; seawater influence  Soil runoff  By product of drinking water chlorination.  Naturally occurring element
Total Hardness  Odor  Sulfate Total Dissolved Solids  Turbidity UNREGULA Chlorate  Molybdenum	grains/ gal TON ppm ppm NTU	NA  NA  3  500  1000  5  NTAMIN  NA	NA NA NA NA NA NA 210	NA 1 0.5 NA NA UCMR3	Range Average Range Average Range Average Range Average Average Range Average Average Average Average Average	200 - 320 283 12 - 19 16 ND ND 191 - 275 249 NA 640 Distrib Distrib 28 - 41 34 4.2 - 4.7	170 - 240 205 10 - 14 12 ND ND 89 - 115 104 NA 430 oution System v ribution System NA 100 NA 3.0	NA 310 NA 18 NA 2 NA 250 NA 690 vide range = 0.0 vide average	290–307 299 17 - 18 17 2 2 237–249 243 639–655 647 95 - 0.40 = 0.10	40-60 50 2-4 3 ND ND 15-18 17 120-218 194	Leaching from natural deposits  Leaching from natural deposits  Naturally occurring organic materials  Runoff/leaching from natural deposits; seawater influence  Runoff/leaching from natural deposits; seawater influence  Soil runoff  By product of drinking water chlorination.
Total Hardness  Odor  Sulfate Total Dissolved Solids  Turbidity  UNREGULA Chlorate  Molybdenum  Strontium	grains/ gal  TON  ppm  ppm  NTU  TED CO  ppb	NA  NA  3  500  1000  5  NTAMIN  NA	NA NA NA NA NA NA JANTS ( 210	NA  1  0.5  NA  NA  UCMRE 20  NA	Range Average	200 - 320 283 12 - 19 16 ND ND 191 - 275 249 NA 640 Distrib Dist 28 - 41 34 4.2 - 4.7 4.4 950 - 1200 1080	170 - 240 205 10 - 14 12 ND ND 89 - 115 104 NA 430 ution System w ribution System NA 100 NA 180	NA 310 NA 18 NA 2 NA 250 NA 690 vide range = 0.0 wide average 130-320 220 NA ND	290–307 299 17 - 18 17 2 2 237–249 243 639–655 647 15 - 0.40 = 0.10	40-60 50 2-4 3 ND ND 15-18 17 120-218 194	Leaching from natural deposits  Leaching from natural deposits  Naturally occurring organic materials  Runoff/leaching from natural deposits; seawater influence  Runoff/leaching from natural deposits; seawater influence  Soil runoff  By product of drinking water chlorination.  Naturally occuring element
Total Hardness  Odor  Sulfate Total Dissolved Solids  Turbidity UNREGULA Chlorate  Molybdenum  Strontium  Vanadium  ADDITIONA	grains/ gal  TON  ppm  ppm  NTU  TED CO  ppb  ppb  ppb	NA  NA  3  500  1000  5  NTAMIN  NA  NA	NA NA NA NA NA NA SANTS ( 210 35 4200	NA  1  0.5  NA  NA  UCMRS  20  NA  NA	Range Average Range Average Range Average Range Average Range Average	200 - 320 283 12 - 19 16 ND ND 191 - 275 249 NA 640 Distrib Distr 28 - 41 34 4.2 - 4.7 4.4 950 - 1200 1080 ND ND	170 - 240 205 10 - 14 12 ND ND ND 89 - 115 104 NA 430 oution System NA 100 NA 3.0 NA 180 ND	NA 310 NA 18 NA 2 NA 250 NA 690 vide range = 0.0 vide average 130-320 220 NA ND ND ND NA	290–307 299 17 - 18 17 2 2 237–249 243 639–655 647 15 - 0.40 9 - 0.10  97 97 NA NA NA NA	40-60 50 2-4 3 ND ND 15-18 17 120-218 194  NA NA NA NA ND ND ND ND NA	Leaching from natural deposits  Leaching from natural deposits  Naturally occurring organic materials  Runoff/leaching from natural deposits; seawater influence  Runoff/leaching from natural deposits; seawater influence  Soil runoff  By product of drinking water chlorination.  Naturally occuring element  Naturally occuring element  Naturally occuring
Total Hardness  Odor  Sulfate Total Dissolved Solids  Turbidity UNREGULA Chlorate  Molybdenum  Strontium  Vanadium  ADDITIONA Alkalinity	grains/ gal  TON  ppm  ppm  NTU  TED CO  ppb  ppb  ppb  ppb  L PARA	NA  NA  3  500  1000  5  NTAMIN  NA  NA  NA  NA  NA  METERS	NA NA NA NA NA NA NA 1ANTS ( 210 35 4200 21	NA 1 0.5 NA NA UCMRE 20 NA NA 3	Range Average Range Average Range Average Range Average Range Average Average Average Average Average Average Average Range Average Range Average Range Average Range Average Range Range Average Range Average Range Average	200 - 320 283 12 - 19 16 ND ND 191 - 275 249 NA 640 Distrit 28 - 41 34 4.2 - 4.7 4.4 950 - 1200 1080 ND ND 98 - 133	170 - 240 205 10 - 14 12 ND ND 89 - 115 104 NA 430 uttion System v ribution System v ribution System NA 100 NA 180 ND	NA 310 NA 18 NA 2 NA 250 NA 690 vide range = 0.0 vide average  130-320 220 NA ND ND ND NA	290–307 299 17 - 18 17 2 2 237–249 243 639–655 647 15 - 0.40 97 97 NA NA NA NA NA ND	40-60 50 2-4 3 ND ND 15-18 17 120-218 194  NA NA NA NA NA NA NA ND ND ND NA	Leaching from natural deposits  Leaching from natural deposits  Naturally occurring organic materials  Runoff/leaching from natural deposits; seawater influence  Runoff/leaching from natural deposits; seawater influence  Soil runoff  By product of drinking water chlorination.  Naturally occuring element  Naturally occuring element  Naturally occuring Industrial waste discharge.
Total Hardness  Odor  Sulfate Total Dissolved Solids  Turbidity UNREGULA Chlorate  Molybdenum  Strontium  Vanadium  ADDITIONA	grains/ gal  TON  ppm  ppm  NTU  TED CO  ppb  ppb  ppb	NA  NA  3  500  1000  5  NTAMIN  NA  NA  NA	NA NA NA NA NA NA SANTS ( 210 35 4200	NA  1  0.5  NA  NA  UCMRS  20  NA  NA	Range Average Range Average Range Average Range Average Range Average Range Average Average Average Average Range Average	200 - 320 283 12 - 19 16 ND ND 191 - 275 249 NA 640 Distrit Dist  28 - 41 34 4.2 - 4.7 4.4 950 - 1200 1080 ND ND ND ND 98 - 133	170 - 240 205 10 - 14 12 ND ND ND 89 - 115 104 NA 430 oution System NA 100 NA 3.0 NA 180 ND	NA 310 NA 18 NA 2 NA 250 NA 690 vide range = 0.0 vide average 130-320 220 NA ND ND ND NA	290–307 299 17 - 18 17 2 2 237–249 243 639–655 647 15 - 0.40 = 0.10  97 97 NA NA NA NA ND 125–130 128	40-60 50 2-4 3 ND ND 15-18 17 120-218 194  NA NA NA NA ND ND ND ND NA	Leaching from natural deposits  Leaching from natural deposits  Naturally occurring organic materials  Runoff/leaching from natural deposits; seawater influence  Runoff/leaching from natural deposits; seawater influence  Soil runoff  By product of drinking water chlorination.  Naturally occuring element  Naturally occuring element  Naturally occuring
Total Hardness  Odor  Sulfate Total Dissolved Solids  Turbidity UNREGULA Chlorate  Molybdenum  Strontium  Vanadium  ADDITIONA Alkalinity	grains/ gal  TON  ppm  ppm  NTU  TED CO  ppb  ppb  ppb  ppb  L PARA	NA  NA  3  500  1000  5  NTAMIN  NA  NA  NA  NA  NA  METERS	NA NA NA NA NA NA NA 1ANTS ( 210 35 4200 21	NA 1 0.5 NA NA UCMRE 20 NA NA 3	Range Average Range Average Range Average Range Average Range Average Average Average Average Average Average Average Range Average Range Average Range Average Range Average Range Range Average Range Average Range Average	200 - 320 283 12 - 19 16 ND ND 191 - 275 249 NA 640 Distrit 28 - 41 34 4.2 - 4.7 4.4 950 - 1200 1080 ND ND 98 - 133	170 - 240 205 10 - 14 12 ND ND 89 - 115 104 NA 430 ution System w ribution System w ribution System NA 100 NA 3.0 NA 180 ND	NA 310 NA 18 NA 2 NA 2 NA 690 vide range = 0.0 wide average  130-320 220  NA ND ND NA ND NA ND NA ND	290–307 299 17 - 18 17 2 2 237–249 243 639–655 647 15 - 0.40 97 97 NA NA NA NA NA ND	40-60 50 2-4 3 ND ND 15-18 17 120-218 194  NA	Leaching from natural deposits  Leaching from natural deposits  Naturally occurring organic materials  Runoff/leaching from natural deposits; seawater influence  Runoff/leaching from natural deposits; seawater influence  Soil runoff  By product of drinking water chlorination.  Naturally occuring element  Naturally occuring element  Naturally occuring Industrial waste discharge.
Total Hardness  Odor  Sulfate Total Dissolved Solids  Turbidity UNREGULA Chlorate  Molybdenum Strontium  Vanadium  ADDITIONA Alkalinity as CaCO <sub>3</sub> Boron	grains/ gal  TON  ppm  ppm  NTU  TED CO  ppb  ppb  ppb  ppb  L PARA  ppm  ppb	NA  NA  3  500  1000  5  NTAMIN  NA  NA  NA  NA  NA  1000(NL)	NA N	NA 1 0.5 NA NA UCMRC 20 NA NA 3 NA 100	Range Average Range Average Range Average Range Average Range Average Range Average Average Average Range Average	200 - 320 283 12 - 19 16 ND ND 191 - 275 249 NA 640 Distrit 28 - 41 34 4.2 - 4.7 4.4 950 - 1200 1080 ND ND 98 - 133 115 NA NA 48 - 82	170 - 240 205 10 - 14 12 ND ND 89 - 115 104 NA 430 uttion System v ribution System v ribution System v n NA 100 NA 180 ND ND 73 - 97 86 NA NA NA 38 - 51	NA 310 NA 18 NA 2 NA 690 vide range = 0.0 vide average 130-320 220 NA ND ND ND NA 120 NA 140 NA	290–307 299 17 - 18 17 2 2 237–249 243 639–655 647 15 - 0.40 97 97 NA NA NA NA ND 125–130 128 130 75–78	40-60 50 2-4 3 ND ND 15-18 17 120-218 194  NA NA NA NA ND ND ND 15-23	Leaching from natural deposits  Leaching from natural deposits  Naturally occurring organic materials  Runoff/leaching from natural deposits; seawater influence  Runoff/leaching from natural deposits; seawater influence  Soil runoff  By product of drinking water chlorination.  Naturally occuring element  Naturally occuring element  Naturally occuring Industrial waste discharge.  Leaching from natural deposits  Leaching from natural deposits
Total Hardness  Odor  Sulfate Total Dissolved Solids  Turbidity UNREGULA Chlorate  Molybdenum Strontium Vanadium  ADDITIONA Alkalinity as CaCO <sub>3</sub> Boron Calcium	grains/ gal  TON  ppm  ppm  NTU  TED CO  ppb  ppb  ppb  ppb  ppb  L PARA	NA  NA  3  500  1000  5  NTAMIN  NA  NA  NA  NA  NA  NA	NA N	NA  1  0.5  NA  NA  20  NA  NA  NA  NA  NA	Range Average Range Average Range Average Range Average Range Average Range Average Average Average Average Average Range Average Average Range Average Range Average Range Average Range Average Range Average Range Average	200 - 320 283 12 - 19 16 ND ND 191 - 275 249 NA 640 Distrib Dist  28 - 41 34 4.2 - 4.7 4.4 950 - 1200 1080 ND 48 - 82 70	170 - 240 205 10 - 14 12 ND ND 89 - 115 104 NA 430 ution System v ribution System v ribution System v nb NA 100 NA 180 ND ND ND ND NA 180 ND ND ND ND ND ND ND ND 180 ND ND ND 184 ND ND ND 185 ND ND ND 186 NA NA 38 - 51	NA 310 NA 18 NA 2 NA 2 NA 690 vide range = 0.0 wide average  130-320 220 NA ND ND NA ND NA ND NA ND NA ND NA ND NA 120 NA NA 140 NA 77	290–307 299 17 - 18 17 2 2 237–249 243 639–655 647 15 - 0.40 = 0.10  97 97 NA NA NA ND 125–130 128 130 75–78 77	40-60 50 2-4 3 ND ND 15-18 17 120-218 194  NA NA NA ND ND ND NA  NA NA ND	Leaching from natural deposits  Leaching from natural deposits  Naturally occurring organic materials  Runoff/leaching from natural deposits; seawater influence  Runoff/leaching from natural deposits; seawater influence  Soil runoff  By product of drinking water chlorination.  Naturally occuring element  Naturally occuring element  Naturally occuring loustrial waste discharge.  Leaching from natural deposits  Leaching from natural deposits
Total Hardness  Odor  Sulfate Total Dissolved Solids  Turbidity UNREGULA Chlorate  Molybdenum  Strontium  Vanadium  ADDITIONA Alkalinity as CaCO <sub>3</sub> Boron  Calcium Heterotrophic	grains/ gal  TON  ppm  ppm  NTU  TED CO  ppb  ppb  ppb  ppb  ppb  ppb  ppb  p	NA  NA  3  500  1000  5  NTAMIN  NA  NA  NA  NA  NA  NA  NA  NA  NA	NA N	NA  1  0.5  NA  NA  20  NA  NA  3  NA  NA  100  NA	Range Average Range Average Range Average Range Average Range Average Range Average Average Average Range Average	200 - 320 283 12 - 19 16 ND ND 191 - 275 249 NA 640 Distrit Dist  28 - 41 34 4.2 - 4.7 4.4 950 - 1200 1080 ND ND ND ND ND ND ND ND ND O Distrit Dist  28 - 47 A.4 A.4 A.4 A.4 A.4 A.4 A.4 A.4 A.7 A.4 A.7 A.7 A.7 A.7 A.8 A.8 A.8 A.9 Distrit A.4 A.9 Distrit	170 - 240 205 10 - 14 12 ND ND 89 - 115 104 NA 430 uttion System w ribution System w ribution System w RA 100 NA 3.0 NA 180 ND 436 NA	NA 310 NA 18 NA 2 NA 2 NA 690 vide range = 0.0 wide average 130-320 220 NA ND ND NA ND NA 120 NA 140 NA 77 wide range = N	290–307 299 17 - 18 17 2 2 237-249 243 639–655 647 15 - 0.40 = 0.10  97 97 NA NA NA ND 125–130 128 130 130 75–78 77	40-60 50 2-4 3 ND ND 15-18 17 120-218 194  NA NA NA NA ND ND ND 15-23	Leaching from natural deposits  Leaching from natural deposits  Naturally occurring organic materials  Runoff/leaching from natural deposits; seawater influence  Runoff/leaching from natural deposits; seawater influence  Soil runoff  By product of drinking water chlorination.  Naturally occuring element  Naturally occuring element  Naturally occuring Industrial waste discharge.  Leaching from natural deposits  Bacteria naturally present in the
Total Hardness  Odor  Sulfate Total Dissolved Solids  Turbidity UNREGULA Chlorate  Molybdenum Strontium Vanadium  ADDITIONA Alkalinity as CaCO <sub>3</sub> Boron Calcium	grains/ gal  TON  ppm  ppm  NTU  TED CO  ppb  ppb  ppb  ppb  L PARA  ppm  ppb	NA  NA  3  500  1000  5  NTAMIN  NA  NA  NA  NA  NA  1000(NL)	NA N	NA 1 0.5 NA NA UCMRC 20 NA NA 3 NA 100	Range Average Range Average Range Average Range Average Range Average Range Average Average Average Range Average	200 - 320 283 12 - 19 16 ND ND 191 - 275 249 NA 640 Distrit Dist  28 - 41 34 4.2 - 4.7 4.4 950 - 1200 1080 ND ND ND ND ND ND ND ND ND O Distrit Dist  28 - 47 A.4 A.4 A.4 A.4 A.4 A.4 A.4 A.4 A.7 A.4 A.7 A.7 A.7 A.7 A.8 A.8 A.8 A.9 Distrit A.4 A.9 Distrit	170 - 240 205 10 - 14 12 ND ND 89 - 115 104 NA 430 uttion System w ribution System w ribution System w RA 100 NA 3.0 NA 180 ND 436 NA	NA 310 NA 18 NA 2 NA 2 NA 690 vide range = 0.0 wide average  130-320 220 NA ND ND NA ND NA ND NA ND NA ND NA ND NA 120 NA NA 140 NA 77	290–307 299 17 - 18 17 2 2 237-249 243 639–655 647 15 - 0.40 = 0.10  97 97 NA NA NA ND 125–130 128 130 130 75–78 77	40-60 50 2-4 3 ND ND 15-18 17 120-218 194  NA NA NA NA ND ND ND 15-23	Leaching from natural deposits  Leaching from natural deposits  Naturally occurring organic materials  Runoff/leaching from natural deposits; seawater influence  Runoff/leaching from natural deposits; seawater influence  Soil runoff  By product of drinking water chlorination.  Naturally occuring element  Naturally occuring element  Naturally occuring loustrial waste discharge.  Leaching from natural deposits  Leaching from natural deposits
Total Hardness  Odor  Sulfate Total Dissolved Solids  Turbidity UNREGULA Chlorate  Molybdenum  Strontium  Vanadium  ADDITIONA Alkalinity as CaCO <sub>3</sub> Boron  Calcium Heterotrophic	grains/ gal  TON  ppm  ppm  NTU  TED CO  ppb  ppb  ppb  ppb  ppb  ppb  ppb  p	NA  NA  3  500  1000  5  NTAMIN  NA  NA  NA  NA  NA  NA  NA  NA  NA	NA N	NA  1  0.5  NA  NA  20  NA  NA  3  NA  NA  100  NA	Range Average Range Average Range Average Range Average Range Average Range Average Average Range Average	200 - 320 283 12 - 19 16 ND ND 191 - 275 249 NA 640 Distrit Dist  28 - 41 34 4.2 - 4.7 4.4 950 - 1200 1080 ND ND 98 - 133 115 NA NA 48 - 82 70 Distrit 19 - 30 26	170 - 240 205 10 - 14 12 ND ND 89 - 115 104 NA 430 ution System v ribution System v ribution System v nb NA 100 NA 180 ND ND 73 - 97 86 NA NA 38 - 51 44 bution System 44 bution System 19 - 28 23	NA 310 NA 310 NA 18 NA 2 NA 250 NA 690 vide range = 0.0 vide average  130-320 220 NA ND ND ND NA 120 NA 140 NA 77 vide range = N wide average NA NA 28	290–307 299 17 - 18 17 2 2 237–249 243 639–655 647 15 - 0.40 = 0.10  97 97 NA NA NA ND 125–130 128 130 75–78 77 D - 380 a = 4 25–27 26	NA	Leaching from natural deposits  Leaching from natural deposits  Naturally occurring organic materials  Runoff/leaching from natural deposits; seawater influence  Runoff/leaching from natural deposits; seawater influence  Soil runoff  By product of drinking water chlorination.  Naturally occuring element  Naturally occuring element  Naturally occuring Industrial waste discharge.  Leaching from natural deposits  Leaching from natural deposits  Leaching from natural deposits  Bacteria naturally present in the environment.  Leaching from natural deposits
Total Hardness  Odor  Sulfate Total Dissolved Solids  Turbidity UNREGULA Chlorate  Molybdenum  Strontium  Vanadium  ADDITIONA Alkalinity as CaCO <sub>3</sub> Boron  Calcium Heterotrophic Plate Count  Magnesium	grains/ gal  TON  ppm  Ppm  NTU  TED CO  ppb  ppb  ppb  ppb  ppb  ppb  CFU/mL  ppm	NA  NA  3  500  1000  5  NTAMIN  NA  NA  NA  NA  TT  NA	NA N	NA  1  0.5  NA  NA  20  NA  NA  3  NA  100  NA  NA  NA	Range Average Range Average Range Average Range Average Range Average Range Average Average Range Average	200 - 320 283 12 - 19 16 ND ND 191 - 275 28-41 34 4.2 - 4.7 4.4 950 - 1200 1080 ND	170 - 240 205 10 - 14 12 ND ND 89 - 115 104 NA 430 ution System v ribution System v ribution System V RA 100 NA 180 ND ND ND NA 180 ND ND 438 - 51 44 bution System 44 bution System 54 19 - 28 23 7.9 - 8.4	NA 310 NA 310 NA 18 NA 2 NA 690 vide range = 0.0 wide average  130-320 220 NA ND ND NA ND NA 120 NA 140 NA 140 NA 77 wide range = N m wide average NA 77 wide range = N m wide average	290–307 299 17 - 18 17 2 2 237–249 243 639–655 647 15 - 0.40 = 0.10  97 97 NA NA NA ND 125–130 128 130 130 75–78 77 D - 380 2 = 4 25–27 26 8.1–8.2	40-60 50 2-4 3 ND ND 15-18 17 120-218 194  NA NA NA ND ND ND ND 030-740 410 15-23 20 0.3-0.6 0.4 8.0-8.7	Leaching from natural deposits  Leaching from natural deposits  Naturally occurring organic materials  Runoff/leaching from natural deposits; seawater influence  Runoff/leaching from natural deposits; seawater influence  Soil runoff  By product of drinking water chlorination.  Naturally occuring element  Naturally occuring element  Naturally occuring lement  Naturally occuring lement  Leaching from natural deposits  Leaching from natural deposits  Leaching from natural deposits  Bacteria naturally present in the environment.  Leaching from natural deposits  Measure of the acidic or basic
Total Hardness  Odor  Sulfate Total Dissolved Solids  Turbidity UNREGULA Chlorate  Molybdenum  Strontium  Vanadium  ADDITIONA Alkalinity as CaCO <sub>3</sub> Boron  Calcium Heterotrophic Plate Count	grains/ gal  TON  ppm  ppm  NTU  TED CC  ppb  ppb  ppb  ppb  ppb  ppb  ppb	NA  NA  3  500  1000  5  NTAMIN  NA  NA  NA  NA  NA  TT	NA N	NA  1  0.5  NA  NA  UCMRE  20  NA  NA  100  NA  NA	Range Average Range Average Range Average Range Average Range Average Range Average Average Range Average	200 - 320 283 12 - 19 16 ND ND 191 - 275 249 NA 640 Distrit Dist  28 - 41 34 4.2 - 4.7 4.4 950 - 1200 1080 ND ND 98 - 133 115 NA NA 48 - 82 70 Distrit 19 - 30 26	170 - 240 205 10 - 14 12 ND ND 89 - 115 104 NA 430 ution System v ribution System v ribution System v nb NA 100 NA 180 ND ND 73 - 97 86 NA NA 38 - 51 44 bution System 44 bution System 19 - 28 23	NA 310 NA 310 NA 18 NA 2 NA 250 NA 690 vide range = 0.0 vide average  130-320 220 NA ND ND ND NA 120 NA 140 NA 77 vide range = N wide average NA NA 28	290–307 299 17 - 18 17 2 2 237–249 243 639–655 647 15 - 0.40 = 0.10  97 97 NA NA NA ND 125–130 128 130 75–78 77 D - 380 a = 4 25–27 26	NA	Leaching from natural deposits  Leaching from natural deposits  Naturally occurring organic materials  Runoff/leaching from natural deposits; seawater influence  Runoff/leaching from natural deposits; seawater influence  Soil runoff  By product of drinking water chlorination.  Naturally occuring element  Naturally occuring element  Naturally occuring Industrial waste discharge.  Leaching from natural deposits  Leaching from natural deposits  Leaching from natural deposits  Bacteria naturally present in the environment.  Leaching from natural deposits

This data table lists all the substances that were detected in the drinking water during 2015 or the most recent sampling prior to 2015. The presence of these substances does not necessarily constitute a health risk.

The table contains the name of each substance, the unit of measurement, the highest level allowed, the ideal goals, the detection level, the amount detected. and the usual source of the substance. Some substances are not tested each year because the concentrations do not vary significantly from year to year. For these substances, the table includes data from the most recent testing done within the past 5 years.


Table Footnotes, Terms and Abbreviations are listed on next page.



# Water Quality Report 2015







#### **TABLE FOOTNOTES**

a) Turbidity is a measure of the cloudiness of the water. We monitor it because it indicates the effectiveness of our filtration system. Treatment plant effluent turbidity is recorded every 15 minutes. The turbidity of the filtered water shall be less than or equal to 0.3 NTU in 95% of the measurements taken each month. Turbidity shall not exceed 1.0 NTU at any time. Turbidity is also tested at 30 locations each month within the distribution system and reported under Secondary Standards.

- b) Aluminum also has a secondary MCL of 200 ppb or 0.2 ppm.
- c) MWD started fluoridation treatment in 2007. Some MWD water is used to supplement Oceanside's treated water. Oceanside does not currently fluoridate during treatment.
- d) Lead and Copper are tested every three years at consumer's taps. It was last tested in 2015. If the Action level is exceeded in 10% of the samples (90th percentile), then the water supplier must modify the treatment process to prevent the leaching of these metals into the water from the plumbing. None of the samples exceeded the Action levels.
- e) No more than 5.0% of all monthly samples taken in the distribution system may be Total Coliform positive. In 2015, there were 1,613 samples taken throughout the City and none were positive.
- f) Analyzed every six years. R.A. Weese sampled 2013, MBDF sampled 2012, MWD (SDCWA) 2014.
- g) California Division of Drinking Water considers 50 pCi/L to be the level of concern for beta particles.
- h) Compliance is based on a location running annual average (LRAA) of 8 distribution system sample locations taken every quarter.
- i) Compliance is based on a running annual average (RAA) of 30 distribution system samples taken each month.
- j) UCMR3 = Unregulated Contaminants Monitoring Rule 3. The EPA requires monitoring in order to determine if there is a need to regulate these compounds. Testing for R.A. Weese and MBDF was completed in 2015. Testing for MWD (SDCWA) was performed in 2014.

### TERMS AND ABBREVIATIONS

AL – Regulatory Action Level, the concentration of a contaminant which, if exceeded, triggers treatment or other requirements that a water system must follow.

CFU/mL - Colony Forming Unit per milliliter, a measure of the amount of all types of bacterial found in the water.

DLR - Detection Limit for purposes of Reporting, the lowest level that can be reliably detected and quantified.

LRAA - Location running annual average.

MCL – Maximum Contaminant Level, the highest level of a contaminant that is allowed in drinking water. Primary MCLs are set as close to the PHGs (or MCLGs) as is economically and technologically feasible. Secondary MCLs are set to protect the odor, taste, and appearance of drinking water.

MCLG – Maximum Contaminant Level Goal, the level of a contaminant in drinking water below which there is no known or expected risk to health. MCLGs are set by the U.S. Environmental Protection Agency.

MRDL – Maximum Residual Disinfectant Level, the highest level of a disinfectant allowed in drinking water. There is convincing evidence that addition of a disinfectant is necessary for control of microbial contaminants.

MRDLG – Maximum Residual Disinfectant Level Goal, The level of a drinking water disinfectant below which there is no known or expected risk to health. MRDLGs do not reflect the benefits of the use of disinfectants to control microbial contaminants.

NA - Not Applicable or not specified

ND - Not Detected

NTU - Nephelometric Turbidity Units, a measure of clarity.

pCi/L - Picocuries per liter, a measure of radiation.

PDWS – Primary Drinking Water Standard, MCLs and MRDLs for contaminants that affect health along with their monitoring and reporting requirements, and water treatment requirements.

PHG – Public Health Goal, the level of a contaminant in drinking water below which there is no known or expected risk to health. PHGs are set by the California Environmental Protection Agency.

ppb – Parts per billion or micrograms per liter

ppm – Parts per million or milligrams per liter

RAA – Running Annual Average, the monthly average of all samples computed each quarter and averaged for four consecutive quarters.

TON – Threshold odor number.

 ${\bf TT-T} reatment\ Technique,\ a\ required\ process\ intended\ to\ reduce\ the\ level\ of\ a\ contaminant\ in\ drinking\ water.$ 

